


WTG-QUANTOR GMBH

WTG-Quantor brands



Fermline - Temperature Control System

FERMFLEX-BOX



NEW MODEL !



FERMFLEX-BOX

The elegant stainless-steel control cabinet **FermFlex-Box** serves to control tanks temperature automatically, from a central point in the wine cellar or in the brewery. For each tank to be controlled a **FermFlex-Box** control card is included. Therefore the temperatures of all tanks can be viewed at a glance and the settings can be changed on the spot.

The **FermFlex-Box** control unit receives its input through a cable-type sensor (available as an accessory) which is placed in the thermo-well of the respective tank. The controllers are designed in such a way that temperatures are optimally visualised: There are two separate displays for the pre-set temperature and the measured temperature (is temperature). The operation mode of the controller - cooling or heating - is indicated on a LED display. Moreover the control cabinet has two integrated relays for pump control: one for heating and one for cooling.

The **FermFlex-Box** control cabinets are equipped with a PC interface so that the temperature settings can be adjusted either physically on the cabinet or in the office using the **Ferm-Software** installed on a Server PC (option). Using the software allows easy and quick analysis of the measured data, data-saving of finished fermentations for later evaluation and archiving. Software access is enabled over lap-top and mobile phone over safe internet access. The new FermLine controllers can be locked by code – single units or the whole installation at once via BUS system - to prevent temperature modification by unauthorized personnel. The **FermFlex-Box** can also be completely integrated in the bus system VinInfo.


The cabinets are available in two different sizes – for 10, for 20 or for 30 controllers (one controller per tank). With this new generation of **FermFlex-Box** it is possible to add more controllers afterwards if the maximum amount of controllers (10 / 20 / 30) is not needed for the initial installation.

SUITABLE FOR INDUSTRIES



CHARACTERISTICS

- Central control cabinet available in three sizes - for up to 10, 20 or 30 tanks
- One pre-installed controller per tank
- Stainless steel casing
- Simple and clear operation
- Informative display with high contrast LED lighting for distance sighting. Simultaneous display of the measured and the set-temperatures, control-mode and the activity
- Temperature indication from -9,9 to +99,9°C, suitable for measuring high temperature processes such as pasteurization, beer mashing, sugar syrup for CSD etc.
- Two integrated collective relays for pump control: one for heating and one for cooling
- Integrated safety backup for data protection during electric power-out
- With PC data interface for control over Ferm-Software
- Can be locked by code – a single controller or the whole installation at once
- Integration into the bus system VinInfo possible



TECHNICAL DATA - CONTROLLER	Temperature range	from -9,9 to +99,9°C (from 14,2 to 211,8°F)
	Output	24V AC / 2,5A
	Regulation structure	2-point (heating or cooling) 3-point (heating and cooling)
	Operation modes	Cooling / Heating / Cooling & Heating / Display / Off

TECHNICAL DATA - CABINET	Power supply	230V / 1Ph / 50-60Hz
	Protection type	IP 55
	Dimensions: WxDxH	FermFlex-Box (10): 600x210x350 mm FermFlex-Box (20): 600x210x500 mm FermFlex-Box (30): 600x210x700 mm
	Weight	FermFlex-Box (10): 20 kg FermFlex-Box (20): 28 kg FermFlex-Box (30): 40 kg

Specifications subject to change.